

Project Title: Construction of El Salvador City “AA” Slaughterhouse

Location: El Salvador City, Misamis Oriental

SLH EQUIPMENT FACILITIES

DESCRIPTION		QTY	UNIT	UNIT COST	TOTAL COST
I: HOG LINE					
1.1	Hog Restrainer: Specifications				
	<ul style="list-style-type: none"> V-Shape type chamber, made of 3mm thk. sus Grade 304 steel plate 	1	set		
A.	<ul style="list-style-type: none"> SuS 304 plate fully welded construction with hand lever unloader, vertical type entrance gate 				
	<ul style="list-style-type: none"> dim. (LxWxH)1800mmx600mmx900mm 				
1.2	Slap Tattooer				
	<ul style="list-style-type: none"> Kenchum or its equivalent with food grade ink, pad and Characters from (A-Z) and (O-9) 	1	set		
1.3	Electric Hog Stunner: Specifications				
A.	<ul style="list-style-type: none"> 220 V AC input, 0-250 Vac output (variable) 1 phase with enclosure, scissor type, includes power switch, safety pilot lamps, contactors and thermal fuses, includes 4 mtrs royal 	1	set		
1.4	Scalding Vat Solid Fired: Specifications				
	6 mm thick SS Grade 304 fully welded construction with 50mm dia SS drain gate valves, lifter, and counter weight	1	set		
A.	<ul style="list-style-type: none"> includes furnace construction w/ fire bricks insulation 1 meter above roof and 250 mm dia heat resistant chimney 				
	dimension: 1800mmLx1200mmWx700mmH				
	Includes ss 304 solid rod (L is 1000mm and 16mm diameter) w/ hook (130mm length)				
1.4A	De-hairing Machine				
	60 hogs per hour capacity, Heavy duty steel structure , stainless grade 304 or higher at least 45 sets of rubbersized paddle assembly with scrapers:	1	set		
	75mm dia. Rotating shaft with cast steel paddle holder				
	Includes unloading cradle with tarp guard with overhead water shower at least 7.5hp electric motor 220VAC, 3 phase, 60 Hz, Chain Drive type.				
1.5	Dehairing Table: Specifications				
	38mm dia stainless steel 304 tubular legs and frame with adjustable base jack	1	pc		
A.	<ul style="list-style-type: none"> 32mm dia stainless steel 304 pipe table top at 150mm spacing at the center and tipping down chute 				

DESCRIPTION		QTY	UNIT	UNIT COST	TOTAL COST
	fully welded construction				
	dimension: 1200mm L x 1000mm W x 600mm H				
1.7	Hog Trolley : Specifications				
	95mm dia roller with tiger bronze bushing/engineering plastic (nylon flesh, hard-type)	35	pc		
	flat bar frame, 10mm x 15mm machine pressed				
	• double swivel axle, assembly is hot dip galvanized finished				
	length: 550mm				
	Wheel axle is with bushing and meat hooks are 12mm dia sus 304				
1.8	Gambrel: Specifications				
	• Made of stainless 304, 530mm total length 16mm gambrel & 8mm lifting lug	35	pc		
1.9	Blow Torch with 11kg LPG Tank, 2m flexible hose, nozzle, regulator with LPG carrier	1	unit		
1.10	Sticking Platform with Blood through				
	• 1.5mm thk ss 304 Elbow-shape type roller conveyor with tipping down chute	1	set		
	• 2" x 3" stainless steel rectangular tube framing along roller with adjustable base jack				
	• 32mm dia stainless steel pipe table top and support at 150mm spacing at the center				
	• fully welded construction				
II: CATTLE LINE					
2.1	Knocking Pen Door w/ Entrance Gate: Specifications				
	made of 150mm channel bar, 2mm thk. sus 304 Plate revolving door , double wall reinforced with angular steel	1	set		
	revolving door mounted on self align pelow block with manual lock/unlock hand lath, 2" thk. X 2.38m W x 1.40m H				
A.	• includes vertical entrance gate made of 3mm thk sus plate w/ steel angle frame and counter weight with metal casing, 5/16 stell cable cord with 2 1/2" dia. Sus pulley				
	includes civil works component (stairs and platform)				
2.2	Captive Volt Stunner: Specification				
	• Kentmaster brand or equivalent	1	set		
	• with 100 rounds cartridge penetrative with velocity of 40 meters/second, includes permitting				
2.3	Electric Hoist with accessories				

DESCRIPTION		QTY	UNIT	UNIT COST	TOTAL COST
A.	1500 kgs capacity	1	set		
	<ul style="list-style-type: none"> includes pendent type push button switch up and down, hoist trolley, 220 vac, single phase or 3 phase, 60 hz, made in US or equivalent, stationary or with rail 				
2.4	Oscillating Platform: Specifications	2	set		
A.	<ul style="list-style-type: none"> SuS 304 checkered plate landing 				
	200 kgs cap, foot operated switches, up and down				
	<ul style="list-style-type: none"> with limit switch, made in Japan or equivalent, 220AC, 60Hz 				
	<ul style="list-style-type: none"> With fix hand & tool dip 				
	<ul style="list-style-type: none"> Dim. (LxWxH) 900x1000x3000mm (travelling height) 				
<ul style="list-style-type: none"> Framing: 3" dia. Guide post, 2" x 2" angular/tubular sus framing, fully welded 					
<ul style="list-style-type: none"> with chain or cable lifting cord 					
2.5	Beef Trolleys	12	pcs		
	<ul style="list-style-type: none"> 110mm dia roller with tiger bronze bushing/engineering plastic (nylon flesh, hard-type) 				
	flat bar frame, 10mm x 15mm machine pressed				
	<ul style="list-style-type: none"> double swivel axle, assembly is hot dip galvanized finished 				
<ul style="list-style-type: none"> length: 600mm 					
Wheel axle is with bushing and meat hooks are 12mm dia sus 304					
2.6	Overhead Railing System: Specifications	45.00	lm		
A.	<ul style="list-style-type: none"> w/ section structural rail support type A36 steel 				
	<ul style="list-style-type: none"> With stainless 304 rod shifter 				
	12mm x 63mm flat bar overhead meat rail and 10mm x 63mm flat bar rail hangers and rail track switches				
	<ul style="list-style-type: none"> with mounting (support) 				
	<ul style="list-style-type: none"> primer coated, enamel finished 				
2.7	Carcass Spreader	1	pc		
	<ul style="list-style-type: none"> 19mm dia ss pipe 1200mm L 				
	driven by 1HP TEFC motor 220V AC, 1 phase, 60Hz, 1750 RPM with speed reducer				
	<ul style="list-style-type: none"> includes NEMA 3r control box with light indicator for reverse stroke 				
<ul style="list-style-type: none"> screw/auger type 					
2.8	Carcass Lowerator	1	pc		
	auger type carcass regulator from high to low dispatch				
	<ul style="list-style-type: none"> rail driven by 0.5HP TEFC motor with speed reducer, 220 vac, 1 phase ,60hz 				
<ul style="list-style-type: none"> screw-type lowerator w/ spindle shaft and blades mounted on block bearings 					

DESCRIPTION		QTY	UNIT	UNIT COST	TOTAL COST
	<ul style="list-style-type: none"> includes magnetic starter with enclosure 				
2.9	Hoof Scalding Vat				
	<ul style="list-style-type: none"> 900mm dia cast iron cauldron includes furnace with SK 32 firebricks insulation and 150mm dia. Chimney with SK 32 firebricks insulation, chimney firebricks extended 1.5m high at the roof top 	1	pc		
2.10	Bleeding Through				
A.	<ul style="list-style-type: none"> Ss 304 25mm dia pipe and 50mm tubular legs and frame Full welded construction Dimension: 1500mm L x 1700mm W x 400mm & 300mm H fixed 	1	set		
III: AUXILIARY EQUIPMENTS					
3.1	Trolley Storage Truck				
	<ul style="list-style-type: none"> 38mm thick stainless steel pipe frames for hog and beef trolley storage with 4 or 6-100mm dia nylon caster for easy transport Dim. LxWxH (1300mm L x 500mm W x 1000mm H) 	1	pc		
3.2	Paunch Truck				
	<ul style="list-style-type: none"> 3mm thick stainless steel tub construction with 1 1/4" dia pipe handle with two fixed nylon wheels and one or two swivel caster wheel includes viscera tilting pan 	1	set		
3.3	Hand/tool Dip Tub				
	<ul style="list-style-type: none"> stainless steel 304 construction with drain pipe equipped with ball valve dim: (LxWxH) 500mm x 350mm x 800mm 1" dia sus pipe/tubular legs and support 	6	pc		
3.4	Plastic Curtain				
A.	<ul style="list-style-type: none"> 4mm thick x 150mm industrial pvc plastic curtain anti-insect yellow includes accessories and installation 	2	roll		
3.5	Overhead Track Scale				
	<ul style="list-style-type: none"> 500kgs capacity, 200gram graduation, digital display indicator, 220v ac, 1 phase, 60hz With printer includes 2 shear type load cell and steel weight section 	1	set		
3.6	Hand Washing Facilities				
	<ul style="list-style-type: none"> includes hand wash lavatory knee operated 1" dia. Pipe/1" x 1" tubular support materials: all stainless steel 304 	3	pc		
3.7	Viscera Inspection Table				

DESCRIPTION		QTY	UNIT	UNIT COST	TOTAL COST
	<ul style="list-style-type: none"> 2mm thick sus 304, Hopper bottom frame and drain 	1	pc		
	<ul style="list-style-type: none"> 38 and 25mm dia sus 304 legs and support with adjustable base jack 				
	<ul style="list-style-type: none"> dim:1000mm L x 600mm W x 800mm H 				
3.8	Offal Hanger	10	lm		
A.	<ul style="list-style-type: none"> 5x50mm sus 304 angle bar for bracket 10 mm dia. For fixed (5hangers/lm) 				
3.9	Carcass Washing Enclosure (optional)	1	set		
	<ul style="list-style-type: none"> 2" x 2" sus 304 angle bar for framing 				
B.	<ul style="list-style-type: none"> Dimensions:1350mm L x 100mm W x 2200 mm H Plastic curtain on 2 sides & plain sheet sus 304 on 1 side 				
3.10	Condemned Receptacle	1	pcs		
	<ul style="list-style-type: none"> dimension: 690mm L x 660mm W X 860mm H 				
	<ul style="list-style-type: none"> 3mm thk. Sus 304 tub construction with 1" x 1" tubular/1" dia. Pipe handle 				
	<ul style="list-style-type: none"> with 4-100mm dia caster wheel made from engineering plastic with lock and cover 				
3.11	Hoof/Hair Remover	12	pcs		
	<ul style="list-style-type: none"> sus 304 cone 70mm diameter and 130mm length with hook 				
3.12	Work Platform	2	pcs		
	<ul style="list-style-type: none"> 1 step, fully weldd 				
	Checkered Plate 3mm thick ss 304				
	300mm H x 500mm W x 800mm L				
	150mm dia. Leg SS 304				
TOTAL					
VAT				5%	
FREIGHT				5%	
TOTAL EQUIPMENT COST					

Prepared by:

Name of Company

Name of Bidder/Authorized Representative

Date